



General Tolerances to DIN ISO 2768

- ✓ The latest DIN standard sheet version applies to all parts made to DIN standards by Waterson Corporation.
- ✓ Variations on dimensions without tolerance values are according to 'DIN ISO 2768-mk'.

General Tolerance for Linear and Angular Dimensions

(DIN ISO 2768 T1)

LINEAR DIMENSIONS

Permissible deviations in mm for ranges in nominal lengths	f (fine)	Tolerance class designation (description)		v (very coarse)
		m (medium)	c (coarse)	
0.5 up to 3	±0.05	±0.1	±0.2	-
over 3 up to 6	±0.05	±0.1	±0.3	±0.5
over 6 up to 30	±0.1	±0.2	±0.5	±1.0
over 30 up to 120	±0.15	±0.3	±0.8	±1.5
over 120 up to 400	±0.2	±0.5	±1.2	±2.5
over 400 up to 1000	±0.3	±0.8	±2.0	±4.0
over 1000 up to 2000	±0.5	±1.2	±3.0	±6.0
over 2000 up to 4000	-	±2.0	±4.0	±8.0

EXTERNAL RADIUS AND CHAMFER HEIGHTS

Permissible deviations in mm for ranges in nominal lengths	f (fine)	Tolerance class designation (description)		v (very coarse)
		m (middle)	c (coarse)	
0.5 up to 3	±0.2	±0.2	±0.4	±0.4
over 3 up to 6	±0.5	±0.5	±1.0	±1.0
over 6	±1.0	±1.0	±2.0	±2.0

ANGULAR DIMENSIONS

Permissible deviations in degrees and minutes for ranges in nominal lengths	f (fine)	Tolerance class designation (description)		v (very coarse)
		m (middle)	c (coarse)	
up to 10	±1°	±1°	±1°30'	±3°
over 10 up to 50	±0°30'	±0°30'	±1°	±2°
over 50 up to 120	±0°20'	±0°20'	±0°30'	±1°
over 120 up to 400	±0°10'	±0°10'	±0°15'	±0°30'
over 400	±0°5'	±0°5'	±0°10'	±0°20'

General Tolerance for Form and Position

(DIN ISO 2768 T2)

STRAIGHTNESS AND FLATNESS

Ranges in nominal lengths in mm	Tolerance class		
	H	K	L
up to 10	0.02	0.05	0.1
over 10 up to 30	0.05	0.1	0.2
over 30 up to 100	0.1	0.2	0.4
over 100 up to 300	0.2	0.4	0.8
over 300 up to 1000	0.3	0.6	1.2
over 1000 up to 3000	0.4	0.8	1.6

PERPENDICULARITY

Ranges in nominal lengths in mm	Tolerance class		
	H	K	L
up to 100	0.2	0.4	0.6
over 100 up to 300	0.3	0.6	1
over 300 up to 1000	0.4	0.8	1.5
over 1000 up to 3000	0.5	0.8	2

SYMMETRY

Ranges in nominal lengths in mm	Tolerance class		
	H	K	L
up to 100	0.5	0.6	0.6
over 100 up to 300	0.5	0.6	1
over 300 up to 1000	0.5	0.8	1.5
over 1000 up to 3000	0.5	1	2

RUN-OUT

Tolerance class		
H	K	L
0.1	0.2	0.5